

# SINGLE PAN GAS FRYER 400mm

GT18

---

- 400mm wide single pan fryer
- 90MJ multi-jet target burner
- Easy clean stainless steel open pan
- 18L oil capacity
- V-tank with cool zone
- 30mm drain valve
- Rear rollers
- Stainless steel exterior
- Easy service
- Fully modular



GT18

## Overall Construction

- Stainless steel pan
- Bull nose welded 1.2mm 304 stainless steel
- Splashback 1.2mm 304 stainless steel
- Side panels 0.9mm 430 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- Vitreous enamelled front panel
- 30mm drain valve
- 63mm dia. heavy-duty 1.2mm 304 stainless steel adjustable legs at front and two rollers at rear
- 2 baskets and stainless steel lid supplied standard

## Controls

- Mechanical thermostat
- Thermostat range 100 – 190°C
- Over-temperature safety cut-out
- Millivolt gas valve system (no electrical supply)
- Flame failure protection

## Cleaning and Servicing

- Open stainless steel pan for easy clean
  - Easy clean basket support bar
  - 30mm drain valve for effective draining
  - Easy clean stainless steel exterior
  - Access to all parts from front of unit
-

# SINGLE PAN GAS FRYER 400mm

GT18

## Specifications

### Production rate

25kg/hr

### Pan size

Oil capacity 18L (32lbs shortening)

Width 305mm

Length 380mm

Oil frying depth 95mm

### Baskets

2 nickel plated wire baskets

140mm W x 335mm D x 145mm H

Nickel plated wire basket grid

### Burners

Multi-jet target burner

### Gas power

90MJ/hr, 25kW

### Gas connection

R 3/4 (BSP) male

40mm from RH side, 24mm from rear

222mm from floor

All units incorporate Natural and

LP gas regulator

### Dimensions

Width 400mm

Depth 812mm

Height 915mm

Incl. splashback 1085mm

### Nett weight

57kg

### Packing data

0.54m<sup>3</sup>, 97kg

Width 870mm

Depth 495mm

Height 1255mm

### Gas types

Available in Natural gas and LP gas, please specify when ordering

Other gas types on request

### Options

Adjustable feet at rear




Extra baskets

Side splash guards

Joining caps

Castors

Gas conversion kits



[moffat.com.au](http://moffat.com.au)

[moffat.co.nz](http://moffat.co.nz)

### Australia

[moffat.com.au](http://moffat.com.au)

### Moffat Pty Limited

Victoria/Tasmania  
740 Springvale Road  
Mulgrave, Victoria 3170  
Telephone +613-9518 3888  
Facsimile +613-9518 3833  
[vsales@moffat.com.au](mailto:vsales@moffat.com.au)

New South Wales  
Telephone +612-8833 4111  
[nswsales@moffat.com.au](mailto:nswsales@moffat.com.au)

South Australia  
Telephone +613-9518 3888  
[vsales@moffat.com.au](mailto:vsales@moffat.com.au)

Queensland  
Telephone +617-3630 8600  
[qldsales@moffat.com.au](mailto:qldsales@moffat.com.au)

Western Australia  
Telephone +618-9413 2400  
[wasales@moffat.com.au](mailto:wasales@moffat.com.au)

### New Zealand

[moffat.co.nz](http://moffat.co.nz)

### Moffat Limited

Rolleston  
45 Illinois Drive  
Izone Business Hub  
Rolleston 7675  
Telephone +64 3-983 6600  
Facsimile +64 3-983 6660  
[sales@moffat.co.nz](mailto:sales@moffat.co.nz)

Auckland  
Telephone +64 9-574 3150  
[sales@moffat.co.nz](mailto:sales@moffat.co.nz)



Cert. No. 6882

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd  
AN.BSE.01.19/1620

an Ali Group Company



The Spirit of Excellence