



# NU Series Self Contained Dice Ice Machines — up to 68kg

**NU 150 AS OX** Dice cube 10g, 22mm x 22mm x 22mm **NUH 150 AS OX** Half dice cube 6g, 10mm x 22mm x 28mm **NUL 150 AS OX** Large dice cube 15g, 28mm x 22mm x 28mm

> Dice cube 10 g W 22 x D 22 x H 22 mm



Half dice cube 6 g W 10 x D 22 x H 28 mm



Large dice cube 15 g W 28 x D 22 x H 28 mm





Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 68kg daily production rate
- 20kg storage bin capacity
- Air cooled version
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Vertical evaporator spray-system technology
- XSafe Natural Sanitation System
- Ergonomic access to ice with sliding disappearing door
- One touch cleaning for time and labour saving
- Resistant stainless steel exterior
- Easy access front condenser air filter
- Routine maintenance visible alarm light on front panel
- Includes removable air filter, ice scoop, water and drain hose






















# NU Series Self Contained Dice Ice Machines — up to 68kg

## **NU 150 AS OX, NUH 150 AS OX, NUL 150 AS OX**









#### moffat.com.au

### Australia Moffat Pty Limited

## Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

## New South Wales

Telephone 02-8833 4111 nswsales@moffat.com.au

#### South Australia


Telephone 03-9518 3888 vsales@moffat.com.au

#### Queensland

Telephone 07-3630 8600 qldsales@moffat.com.au

#### Western Australia

Telephone 08-9413 2400 wasales@moffat.com.au



## UNIT OF MEASUREMENT: mm

- 1. 25/32" OD OVERFLOW DRAIN
- 2. 3/4" GAS WATER INLET
- 3. 3/4" GAS WATER OUTLET (WATER COOLED UNIT ONLY
- 4. 3/4" GAS WATER INLET (WATER COOLED UNIT ONLY)
- 5. CORD SET

## Ice production per 24 hours

Ambient temperature / Water temperature

	10°C / 10°C	21°C / 10°C	32°C / 21°C
NU 150 AS OX	85	68	48
NUH 150 AS OX	85	70	50
NUL 150 AS OX	80	70	50

## Dimensions

Width: 600mm Depth: 610mm

Height: 770mm (including feet)

Nett weight: 50kg Packed weight: 62kg

## Water consumption Air cooled version:

NU 150 AS: 3.3 litres per hour

NUH 150 AS, NUL 150 AS: 3.4 litres per hour

## Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 500W,

10A cordset supplied

No. Circuit wire: 3

Compressor: 990W Energy consumption: 9.7kW/24hr

Refrigerant type

R404a

### Installation distance from wall

Rear 100mm Sides 150mm

Operating requirement air temperature 10-43°C

## Water connection requirements

Inlet connection: R ¾"
Cold water: 5-38°C
Pressure: 100-500kPa
Water outlet connection: Ø ¾"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd

an Ali Group Company

